



Image 3D

Services & Print

PC-ISO

PC-ISO (polycarbonate-ISO), an industrial thermoplastic, which in its raw state, is biocompatible (ISO 10993 USP Class VI)* and can

be gamma or EtO sterilized. PC-ISO is commonly used in food and drug packaging and medical device manufacturing because of the

material's strength and medical compatibility.

MECHANICAL PROPERTIES ¹		TEST METHOD	ENGLISH	METRIC
Tensile Strength (Type 1, 0.125", 0.2"/min)		ASTM D638	8,300 psi	57 MPa
Tensile Modulus (Type 1, 0.125", 0.2"/min)		ASTM D638	289,800 psi	2,000 MPa
Tensile Elongation (Type 1, 0.125", 0.2"/min)		ASTM D638	4%	4%
Flexural Strength (Method 1, 0.05"/min)		ASTM D790	13,100 psi	90 MPa
Flexural Modulus (Method 1, 0.05"/min)		ASTM D790	310,400 psi	2,100 MPa
IZOD Impact, notched (Method A, 23°C)		ASTM D256	1.6 ft-lb/in	86 J/m
IZOD Impact, un-notched (Method A, 23°C)		ASTM D256	1 ft-lb/in	53 J/m

THERMAL PROPERTIES ²		TEST METHOD	ENGLISH	METRIC
Heat Deflection (HDT) @ 66 psi		ASTM D648	271°F	133°C
Heat Deflection (HDT) @ 264 psi		ASTM D648	260°F	127°C
Glass Transition (Tg)		DMA (SSYS)	322°F	161°C
Vicat Softening		ISO 306	282°F	139°C
Melt Point	-----		Not Applicable ³	Not Applicable ³

ELECTRICAL PROPERTIES ⁴		TEST METHOD	VALUE RANGE
Volume Resistivity		ASTM D257	1.5x10e14 - 8.0x10e13 ohm-cm
Dielectric Constant		ASTM D150-98	3.0 - 2.8
Dissipation Factor		ASTM D150-98	.0009 - .0005
Dielectric Strength		ASTM D149-09, Method A	370 - 70 V/mil



OTHER ²		TEST METHOD	VALUE
Specific Gravity		ASTM D792	1.2
Flame Classification		UL 94	HB